



CISTER

Research Center in
Real-Time & Embedded
Computing Systems

Demo

A module for the FT-SE protocol in ns-3

Fábio Oliveira

Ricardo Garibay-Martínez

Tiago Cerqueira

Michele Albano

Luis Lino Ferreira

CISTER-TR-150407

2015/05/13

A module for the FTT-SE protocol in ns-3

Fábio Oliveira, Ricardo Garibay-Martínez, Tiago Cerqueira, Michele Albano, Luis Lino Ferreira

CISTER Research Center

Polytechnic Institute of Porto (ISEP-IPP)

Rua Dr. António Bernardino de Almeida, 431

4200-072 Porto

Portugal

Tel.: +351.22.8340509, Fax: +351.22.8321159

E-mail: 1090566@isep.ipp.pt, rgmaz@isep.ipp.pt, 1090678@isep.ipp.pt, mialb@isep.ipp.pt, llf@isep.ipp.pt

<http://www.cister.isep.ipp.pt>

A module for the FTT-SE protocol in ns-3

Fábio Oliveira, Ricardo Garibay-Martínez, Tiago Cerqueira,
Michele Albano, Luis Lino Ferreira
CISTER, ISEP/INESC-TEC
Rua Dr. António Bernardino de Almeida 431
4249-015, Porto, Portugal
+351 228340502

EXTENDED ABSTRACT

The Flexible Time Triggered Switched Ethernet (FTT-SE) protocol allows the concurrent transmission of both real-time (i.e., synchronous and asynchronous) traffic and best-effort traffic over Ethernet. Communications within an FTT-SE network are done based on the reservation of fixed duration time slots called Elementary Cycles (ECs). The construction of the ECs and the media access control are managed by the master node. The FTT-SE protocol uses the master/slave paradigm, in which the slave nodes make petitions for transmission to the master node, and the master node grants them access for transmission according to the scheduling algorithm chosen by the master node (e.g., Rate Monotonic, Earliest Deadline First, etc.).

In current automotive applications, tens of electronic control units are interconnected by different network technologies. But such technologies only provide low transmission and processing power. In the future, applications will require larger bandwidth to comply with new functionalities in the car as infotainment and driver-assistance applications. Those applications will require a network that conciliates the transition of best-effort traffic and real-time traffic. Other Real-Time Ethernet (RTE) protocols have been proposed for vehicular networks (e.g. TTEthernet, AV-Bridges, etc.), but they are not flexible enough (e.g. TTEthernet does not support the transmission of asynchronous traffic). The FTT-SE protocol provides communications with real-time guarantees, which is an extremely important characteristic when designing complex real-time distributed systems [1]. Figure 1 shows an example of automotive application in which transmissions are based on the FTT-SE Protocol.




Figure 1 Automotive application based on a FTT-SE network

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from Permissions@acm.org.
WNS3 2015, May 13 2015, Barcelona, Spain

In this demo, we present the module for the implementation of the FTT-SE protocol in ns-3. The current implementation of the FTT-SE module is done as an application layer of ns-3. Currently, the module allows for concurrent synchronous, asynchronous and best-effort communications. The ECs are divided into sub-windows; those sub-windows are dedicated to the transmission of the different types of traffic. The types of traffic in the FTT-SE protocol are: (i) synchronous traffic (with priority 1, the highest); and (ii) asynchronous traffic, the asynchronous traffic is has three different types of traffic: (a) hard

real-time (with priority 2); (b) soft real-time (with priority 3); and (c) best-effort (with priority 4, the lowest). All types of traffics can be transmitted in a single EC which is built by the master node. Furthermore, the percentage of the EC dedicated to the synchronous or asynchronous transmission is tunable and can be decided based on the application needs.

The proposed demo on FTT-SE ns-3 module plans to provide: simulated communication of real-time data over Ethernet that can be visualized through Netanim; Wireshark of the traced packets; statistics on delay/comparison with vanilla Ethernet approach; overview of the code, which will be delivered for the NS-3 review by the end of the summer. By the end of April 2015, the current state of the code will be available on:

<https://bitbucket.org/micheleISEP/fttse-ns3>

ACKNOWLEDGMENTS

This work was supported by the Portuguese Agency for Innovation (ADI) under the ERDF (European Regional Development Fund) through COMPETE (Operational Programme 'Thematic Factors of Competitiveness'), within project

CARCODE, ITEA2 Nr. 11037, QREN - SI I&DT Nr. 30345; by National Funds through FCT/MEC (Portuguese Foundation for Science and Technology) and when applicable, co-financed by ERDF under the PT2020 Partnership, within project UID/CEC/04234/2013 (CISTER Research Centre); also by FCT/MEC and ERDF through COMPETE, within project FCOMP-01-0124-FEDER-020447 (REGAIN); by FCT/MEC and the EU ARTEMIS JU within project ARTEMIS/0001/2012 - JU grant nr. 332987 (ARROWHEAD); by FCT/MEC and ESF (European Social Fund) through POPH (Portuguese Human Potential Operational Program), under PhD grant SFRH/BD/71562/2010.

REFERENCES

Ricardo Garibay-Martínez, Geoffrey Nelissen, Luis Lino Ferreira, Paulo Pedreiras, Luís Miguel Pinho, "Holistic Analysis for Fork-Join Distributed Tasks supported by the FTT-SE Protocol," in Proc. of the 11th IEEE World Conference on Factory Communication Systems, (to be presented in May 2015)